

prostore

Top performing
refrigerated cabinets,
only 700 mm depth



Thinking of you
Electrolux

prostore

The new generation offers unmatched capacity, increased energy efficiency and silent operation.



Capacity

Up to 65 liters more space*

The new **prostore** provides the highest net capacity in the market. Additionally, its 700 mm depth fits with tables and refrigerated counters optimizing the kitchen layout.



Efficiency

55% less energy consumption*

prostore guarantees lower running costs and respects the environment. Assures excellent performance and longer life thanks to the use of R290 natural refrigerant gas and Cyclopentane isolating foam.



Silent Operation

50% lower noise level*

Designed for a kitchen yet perfect for a library. **prostore** guarantees a better working environment.

*compared to equivalent refrigerated cabinets.



prostore 500

Top performing with only 700 mm depth.



prostore 800



- **700 mm depth**
Perfectly aligned in your kitchen layout with Electrolux Professional tables and refrigerated counters



- **Frontal door lock**
provides additional security



- **65 mm insulated walls**
and the improved gasket design assure **low energy consumption**



- ▶ **1/1 GN containers**
prostore 500 cabinets accommodate one 1/1 GN container per grid



- **2/1 GN containers**
prostore 800 cabinets accommodate two 1/1 GN container per grid



- ◆ **Foot pedal**
For easy and fast operations even with busy hands





Internal LED light ■

LED is the lowest energy consumption type of light



Hidden evaporator ■

for maximum internal capacity



Removable ■

wide "balloon" profiled **gasket**, with triple insulation area, provides an **excellent seal** thus **reducing heat dispersion**



IPX5 water protection ■

Full frontal water-proof design



Cook&Chill ▶

prostore 500 is compatible with the 10 1/1 GN cook&chill solution



prostore Premium 500



1 full door



2 - 1/2 doors



1 glass door

Gross capacity - lt	470	470	470
Advanced digital display	•	•	•
LED light	•	•	•
Door LED light			•
Operating temperature at 43 °C	0 +10 / -15 -22	0 +10 / -15 -22	
Operating temperature at 32 °C			0 + 10
Remote cooling unit	•		
Refrigerant	R134a/R404a/R290	R290	R290
Cyclopentane insulation	•	•	•
Defrost type	Frost Watch Control	Frost Watch Control	Frost Watch Control
External and internal panels in AISI	304	304	304
External dimensions - mm (wxdxh)	600x700x2040	600x700x2040	600x700x2040

prostore Premium 800



1 full door



2 - 1/2 doors

Gross capacity - lt	720	720
Advanced digital display	•	•
Internal light	•	•
Operating temperature at 43 °C	0 +10 / -15 -22	0 +10 / -15 -22
Remote cooling unit*	•	
Refrigerant	R134a/R404a/R290	R290
Cyclopentane insulation	•	•
Defrost type	Frost Watch Control	Frost Watch Control
External and internal panels in AISI	304	304
Ice cream model	•	
External dimensions - mm (wxdxh)	900x700x2040	900x700x2040